

LL-230 Loadlogger

FOR LOAD MEASUREMENT AND PROFILING ON DISTRIBUTION CIRCUITS



The LoadLogger is a rugged recording ammeter for non-invasive recording of distribution line currents. Using a hot stick, the LoadLogger clamps onto overhead lines up to 69 kV and can record up to 1000 amps with 1 amp resolution. Up to 66 days of load data can be stored by the LoadLogger and then downloaded to a personal computer where the data is analyzed with LoadSmart® software. The LoadLogger provides continuous load recordings for current versus time load profiling.

Applications:

- Load Growth Studies
- Peak Load Values and Times
- Time of Day Load Fluctuations
- Phase and Load Imbalance on a circuit
- Accurate and Complete input to Distribution System Modeling Programs
- Fuse, Transformer & Equipment Sizing
- Theft of Service Investigations
- Evaluating Circuits for Distribution Automation Projects

LoadSmart® 4

LoadSmart is a powerful tool for analyzing data from the LoadLoggers and Load Profilers. The software allows the user to setup and retrieve data from the recorders.


- Compatible with all our LoadLoggers: LL-210, LL-220, LL-230, LL-230A, and LP-260 Loadprofiler.
- Obtain Maximum & Minimum Values
- Add, subtract, or average time coincident files
- Export to spreadsheet



LL-230 with Display attached

Benefits:

- Non-invasive clamp-on unit
- Voltages up to 69 KV
- Simple to Use
- Lightweight, compact design, Only 5 pounds
- Records up to 1000 Amps with 1 amp resolution.
- Time stamped current profile
- Selectable recording intervals
- Up to 66 days of storage



LoadSmart® 4 Load Profile Graph

AMETEK®

**POWER
INSTRUMENTS**

SPECIFICATIONS

LL-230A
LOADLOGGER

Conductor Size: 0.2 to 1.093 inches diameter (Max. 795 MCM). A rubber adapter is used for bare or insulated conductor diameter 0.2 to 0.4 inches.

Max. Conductor Voltage: 69 kV

Current Range: 0-1000 amps

Battery Life:

Lithium: 2-3 years average
Can be supplemented by a standard 9 V alkaline battery.

Resolution: 1 Amp

Accuracy: <5% of reading
Internal Clock Accuracy: One minute per 2 weeks over specified temperature range.

Operating Temperature Range: -40°C to +55°C

Weight: 5.0 lbs. (2.3 kg) nominal

Environment:

Lifetime warranty for water-resistance

Memory:

Recording memory is user selectable to stop when full or continuously record on a first-in, first-out basis.

Data storage capacity is determined by averaging interval selected.

Averaging Interval	Maximum Storage
15 min.	66 days
5 min.	22 days
1 min.	4.5 days

LL-233

Computer Interface Adapter

RS-232 Connector: Standard 9 pin D-type female connector.

Power:

120 VAC adapter or 9 V alkaline battery – (220VAC on request)

Battery Check: Voltage level factory set to 6.95 V to verify life of lithium battery in LL

LL-234
LCD Module

Display Type: Liquid Crystal – Display
1" high digits

Update Frequency: Display is updated every 3 seconds.

Mounting: Attached to LoadLogger at the serial interface connector.

Power Supply: Operates directly from the LoadLogger's battery.

Operating Temperature: 0°C to +40°C

Dimensions: 5.84 x 2.5 x 1.3 inches (150mm x 64mm x 34mm) nominal

LoadLogger Ordering:

- LL-230 Single Unit
- LL-231 3 Phase Starter Kit (3) LL-230 LoadLoggers, LL-233, LL-234, LoadSmart Software, Carrying case & Manuals
- LL-232 3 Phase Expansion Kit (3) LL-230 LoadLoggers Carrying case & Manuals

Load Profiler Ordering:

- LP-260 Single Unit
- LP-261 3 Phase Starter Kit (3) LP-260 Load Profilers LL-233, LoadSmart Software & Manuals
- LP-262 1 Phase Starter Kit (1) LP-260 Load Profiler LL-233, LoadSmart Software & Instruction Manuals
- LP-261 3 Phase Kit (3) LP-260 Loadprofilers

LP-260
LOADPROFILER



The Load Profiler is a rugged, non-invasive digital recording ammeter for simple, cost effective collection of load data on your power circuits. The Load Profiler has the same operating characteristics as the LL-230, but is packaged for use as a hand held ammeter. To monitor and record line currents, clip the split core current transformer (CT) to any conductor up to 700 volts or any insulated cable up to 2" in diameter – even underground distribution cables.

Specifications:

Same as LL-230A with the following exceptions:

Accuracy: +/- 3% Reading

Temperature Range:

-30°C to 55°C up to 800 Amps

-30° to 30°C up to 1000 Amps

(Display operation: 0° to 40°C)

Cable: Up to 2" outside diameter

Dimensions:

Housings: 3" x 2" x 6"

Cable: 4" Outside Diameter

Cord: 6 feet long

Weight: 1.7 lbs.



For customer support call:

POWER INSTRUMENTS

255 North Union Street
Rochester, NY 14605
Tel: 585.263.7700
Fax: 585.262.4777
power.industrial@ametek.com

HEADQUARTERS

AMETEK Power Instruments
50 Fordham Road
Wilmington, MA 01887
Tel: 978.988.4903
Fax: 978.988.4990
power.industrial@ametek.com

EUROPEAN HEADQUARTERS

Unit 20, Ridgeway
Donibristle Industrial Estate
Dalgety Bay, Dunfermline, KY119JN
Scotland U.K.
Tel: 44.1383.825630
Fax: 44.1383.825715
ametek@scotland.fsnet.co.uk

ASIA PACIFIC HEADQUARTERS

10 Ang Mo Kio Street 65
#05-12 Techpoint
Singapore 569059
Tel: 65.484.2388
Fax: 65.481.6588

