



# Ci20 Electric Revenue Meter

FOR COMMERCIAL AND INDUSTRIAL APPLICATIONS



## REVENUE METER

AMETEK's Ci20 Revenue Meter watches over your energy investment in many ways. It has high accuracy measurements, site diagnostics and dependable communication options to ensure maximum reliability. Your installation investment is reduced with our innovative software wizard that provides quick set-up and configuration. Inventory and ordering is simplified with field upgradeable options using soft switches and plug in boards.

### **High Accuracy Measurements**

The AMETEK Ci20 provides an impressive 0.15% accuracy on watt-hours. Per phase and system measurements are available for all energy and instantaneous readings. The AMETEK Ci20 comes with 4 channels of Load Profile, upgradeable to 12 channels and includes Four Quadrant and Bi-directional measurements.

### **Multiple Communication Choices**

The Ci20 can be equipped with dual serial outputs, or single serial output with Modem or Ethernet ports. The front optical port is standard on all meters. Support is provided for DNP, Modbus, ANSI tables and MV90.

### **Quick Installation and Upgrades**

The Windows based CiSET software configuration wizard reduces configuration time and minimizes errors with the step by step process. Options can be easily added via soft switch or plug in option boards. Order one standard configuration and upgrade it easily at your site to support any installation needs.

### **Graphic Display**

The Ci20 has a large easy to read graphic LCD display for displaying any metered value, health status, alarms and general operation. The secure menu driven display provides access to your meter configurations for quick changes.

### **Site Diagnostics**

The AMETEK Ci20 will determine whether the meter is properly connected through the Installation Verification mode, which displays the per phase measurements and phase vectors on the graphic LCD display. Once installed, the Ci20 continuously checks the operating conditions against pre-set



thresholds with alarms triggered for local or remote notification. The meter can phone any number upon an alarm including a complete power loss, providing quick notification of outages.

### **Continuous Power**

The Ci20 can be equipped to operate off any phase, preventing a loss of recording when one or two phases are dropped. Combined with the site monitoring feature, notification of this event can be provided via automatic modem call, alarm contact and meter reads.

### **Digital I/O**

The Ci20 has 6 channels that can be selected as configurable inputs or KYZ outputs. The inputs can also be wetted through our internal isolated supply.

### **Power Quality**

The Ci20 can monitor and report your site's power quality conditions with sag and swell recording, THD, power factor, imbalance and frequency measurements.

### **Totalization**

With up to 6 configurable inputs, you can totalize a variety of measurements providing a consolidated output.

**AMETEK®**



Experience the Power™

## SPECIFICATIONS

### METER FORMS

Meter Forms: 5,6,8,9,26,35S

### INPUTS

#### Voltage

- 55-530 VAC auto-ranging
- Burden\*: 0.5 VA @ 530V  
\*Does not include auxiliary power requirements.

#### Current

- 10 Amps: ANSI Class 20
- Burden: 0.5 VA maximum
- Overload: 1.5x rated class current continuous, 20x rated class current for 0.50 sec
- Frequency range: 45-55 Hz, 55-65 Hz

### AUXILIARY POWER

55 – 530 VAC

- Derived from A-phase voltage input
- Auxiliary Power Burden
- 15 VA maximum

### ACCURACY

#### Watt-hour

- 0.15% reading

#### Clock

- Synchronized to line or +3 minutes per month maximum error

### MEASUREMENTS

#### Energy PolyPhase Quantities

- Watthour, VARhour, VAhour, Amphour, Amp<sup>2</sup>hour, Volt<sup>2</sup>hour, Qhour

#### Instantaneous Quantities

- System: Watts, VARs, Quadrant Vars, VA, Q, PF, Volts, Amps, Amps<sup>2</sup>, Average Volts,

#### 4 Quadrant Bi-Directional

### REGISTERS

#### 15 Normal or Alternate Using Any Measurements Above

#### Demand Registers

- Fixed or sliding window
- Interval length: 1-60

### LOAD PROFILE

#### 4 Channels of Storage (Standard)

#### Programmable Interval

- 1-60 minutes

#### 64 Days Storage Using Four Channels at 15-minute Intervals

### MECHANICAL

#### Case Styles

- S base and A Base

#### Size and Weight

- S base: 4.5 pounds
- A-base: 6.5 pounds

### COMMUNICATIONS

#### Optical Port (Standard)

- Type 2 – 19,200 Baud
- JEM Binary

### ENVIRONMENT

#### Operating Temperature

- -22° to 185°F (-30° to 85°C)

#### Storage Temperature

- -40° to 185°F (-40° to 85°C)

#### Humidity

- 5 to 95% relative humidity, non-condensing

#### Surge Withstand (SWC)

- ANSI Standard C62.41

#### Fast Transient

- 4kV inputs, 2kV I/O (IEC 61000-4-4)

#### EMC

- FCC Part 15, Class B, FCC Part 68

### STANDARDS

#### Agency Standards and Certifications:

- ANSI Standard C12.1-2001
- ANSI Standard C12.18-1996
- ANSI Standard C12.19-1997
- ANSI Standard C12.20-2002
- Measurement Canada

## METER OPTIONS AND UPGRADES

### MEASUREMENT PLUS

Additional 15 or 35 Measurements (Base Meter Includes 15)

### PER PHASE MEASUREMENT

#### Energy Per Phase Quantities

- Watthour, VARhour, VAhour Amphour, Amp<sup>2</sup>hour, Volt<sup>2</sup>hour, Qhour

#### Instantaneous Per Phase Quantities

- Watts, VARs, Quadrant Vars, VA, Q, PF, Volts, Amps, Neutral Current, Volts<sup>2</sup>, Amps<sup>2</sup>

### TIME OF USE

9 Rates, 20 Year Calendar

### CONTINUOUS POWER

Receives Power from any one of the Three Phases-Guarantees Revenue Capture when a Phase is Dropped

### SITE MONITORING

Set Alarms for Under/Over Voltage and Current, Power Factor. Trigger an Alarm Contact or Phone any Number

Display Site Vector Diagrams Locally or Remotely for Correct Installation

### DEMAND PREDICTION

Determines in Advance When Demand will Exceed Pre-set Threshold

### LOAD PROFILE +

12 Channels of Storage (61 Days @ 15 Minute Intervals)

### ALARM THRESHOLDS

Set Alarms for any Energy or Instantaneous Measurement

Trigger an Alarm Contact or Phone any Number

### COMMUNICATIONS

#### One Comm option board per meter

#### Serial Port Board

- Single or dual serial port
- Field selectable for RS-232 or RS-485
- User configurable: 300 to 38400 baud

#### Internal Modem Board

- 2,400 baud
- With optional serial port (RS-232/485)
- With optional phone home on power fail

#### Ethernet Board

- 10 baseT, unshielded twisted pair
- Up to 4 simultaneous connections
- With optional serial port (RS-232/485)

#### Communication Protocols

- Modbus ASCII or RTU
- DNP 3.0

### TOTALIZATION

Up to 6 Contact Inputs (from Digital Input/Output Board)

Up to 12 Totalization Measurements Displayed and Recorded

### INPUT/OUTPUT BOARD

Six Channels Individually Selectable for a Form-A Contact Input or KYZ Solid-state Output.

#### Contact Inputs (wet or dry)

- User-configurable for: pulse counter, interval synchronization pulse, TOU rate override, status input, totalization
- Customer wetted contact – maximum voltage 40 VDC
- Customer dry contact – optional internally powered 12 VDC

#### Solid-state Outputs

- User-configurable for: any consumption quantity, energy pulse (KYZ), site monitor alarm, threshold alarm, demand sync, voltage sag/swell alarm, system error alarm
- Maximum open-circuit voltage: 200 VDC or Peak AC
- Maximum switching current: 50 mA

### POWER QUALITY

Configurable Thresholds for Voltage Sags and Swells per Phase

Records Start and Duration in Cycles

Records Min/Max/Avg Voltage and Current per Phase, Avg Power Factor Stores Up to 100 Events

Maximum Event Length of 600 Cycle



For customer support call:

### POWER INSTRUMENTS

255 North Union Street  
Rochester, NY 14605  
Tel: 585.263.7700  
Fax: 585.454.7805  
power.sales@ametek.com

### HEADQUARTERS

AMETEK Power Instruments  
50 Fordham Road  
Wilmington, MA 01887  
Tel: 978.988.4903  
Fax: 978.988.4990  
power.sales@ametek.com

### EUROPEAN HEADQUARTERS

Unit 20, Ridgeway  
Donibristle Industrial Estate  
Dalgety Bay, Dunfermline, KY119JN  
Scotland U.K.  
Tel: 44.1383.825630  
Fax: 44.1383.825715  
power.sales@ametekuk.com

### ASIA PACIFIC HEADQUARTERS

10 Ang Mo Kio Street 65  
#05-12 Techpoint  
Singapore 569059  
Tel: 65.6484.2388  
Fax: 65.6481.6588

